

# ARX 10.1

## LIGHT TANDEM VIBRATORY ROLLER

EU STAGE V / U.S. EPA PHASE III

### APPLICATIONS

- Small and medium construction sites
- Road maintenance
- City street repairs
- Confined work spaces
- Pathways
- Playgrounds, golf courses



### PRODUCTIVITY

#### Smart design

that provides diverse benefits to enhance machine performance and overall productivity.

A single-stage vibratory system makes the machine an invaluable tool on the jobsite, delivering optimal **compaction performance**.

### ERGONOMICS

#### The operator platform

is designed for comfort, ensuring a pleasant experience no matter the duration of the shift.

The **operator station** offers 360° visibility to maximize safety on the jobsite.

### SERVICEABILITY

#### Low downtime

Robust design that protects components.

#### Reduced maintenance

Easy-to-reach maintenance points.

### SUSTAINABILITY

#### ECOdrop

Improved efficiency, reduced use of fluids.

#### Advanced technologies

Machine usage controlled to bring efficiency, productivity – and enable precise documentation.

### OPTIONAL EQUIPMENT

- Additional documentation printed
- Additional lights for hard canopy
- Additional Lights for ROPS
- Additional mirror
- AmmannCare Gold
- AmmannCare Silver
- AmmannCare Platinum
- AmmannCare Diamond
- Back-up alarm
- Back-up alarm adaptive
- CE conformity
- Certificate of origin
- Color scheme customer
- Frame ROPS
- Hard canopy ROPS mounted
- Hydraulic oil biodegradable
- Maintenance kit 100h
- Overseas shipping preparation
- Seat activation warning switch
- Seat belt 3"
- Telematics ServiceLink Light
- Toolset
- Warning beacon LED for hard canopy
- Warning beacon LED for ROPS
- Water tank lock
- Working lights

### STANDARD EQUIPMENT

- 1 amplitude / 1 frequencies
- Ammann color design and decals
- Articulation joint with oscillation
- Operator station with one drive lever (RH)
- Two non-split drums, in-line
- Open platform with safety handles
- Front and rear side free drum attachment
- Mechanical drive lever
- Pressure water sprinkling with interval switch, 2 stage filtration
- Horizontally adjustable driver's seat
- Multi-functional display for machine overview
- Fixed scrapers
- Standard hydraulic oil
- Central lifting point

# ARX 10.1

StV/Phase III



## WEIGHT & OPERATING CHARACTERISTICS

OPERATING WEIGHT	1 310 kg (2,888 lb)
OPERATING WEIGHT MAX.	1 398 kg (3,082 lb)
STATIC LINEAR LOAD AVG.	7.2 kg/cm (40.3 lb/in)
MAX. WORKING SPEED	7.9 km/h (4.9 MPH)
GRADEABILITY WITHOUT VIBRATION	30%
GRADEABILITY WITH VIBRATION	30%
TURNING RADIUS (INNER)	2 470 mm (97.2 in)

## ENGINE

MANUFACTURER	Honda
ENGINE TYPE	GX630
ENGINE SPEED	3400 rpm
POWER OUTPUT SAE J1995	15.5 kW / 21HP
EMISSION STAGE	EU Stage V / U.S. EPA Phase III

## COMPACTION FORCES

FREQUENCY I	76 Hz (4560 vpm)
CENTRIFUGAL FORCE I	16.4kN (3687 lbf)
AMPLITUDE I	0.5 mm (0.020 in)

## MISCELLANEOUS

BRAKES OPERATING	Hydrostatic
BRAKES PARKING	Multiple-disc spring brake
BRAKES EMERGENCY	Multiple-disc spring brake
FUEL TANK CAPACITY	30 l (7.9 gal)
WATER TANK CAPACITY	110 l (29.1 gal)
TYPE OF WATERING	Pressure
HYDRAULIC TANK CAPACITY	15 l (4 gal)
STEERING ANGLE	±33°
OSCILLATION ANGLE	±5°
BATTERY VOLTAGE	12V
BATTERY CAPACITY	55 Ah

## MAXIMUM RECOMMENDED COMPACTED LIFT THICKNESS AT OPTIMAL WORKING CONDITIONS

ROCKFILL	-
SAND / GRAVEL	150 mm (6 in)
MIXED SOILS	100 mm (4 in)
SILT	-
CLAY	-
STABILISATION	80 mm (3 in)
ASPHALT	60 mm (2 in)

ARX 10.1

For additional product information and services please visit: [www.ammann.com](http://www.ammann.com)  
Materials and specification data are subject to change without notice.  
MSS-3080-03-EN-US | © Ammann Group

**AMMANN**